



MODEL 300/320

AUTOMATIC CHLORINE/BROMINE FEEDERS

The efficient, easy way to sanitize your pool or spa.

Pentair Models 300 and 320 feeders not only save time but also reduce manual handling of chemicals. They use large or small trichlor or bromine slow-dissolving tablets to make sanitizing your new or existing pool or spa easy and automatic. Both install easily on the pressure side of the pump, downstream of the filter and heater.

The freestanding Model 300 feeder and the in-line Model 320 feeder both feature an external fine-control valve that lets you adjust the feed rate to meet specific pool or spa requirements. The Model 300 feeder is ideal for retrofitting existing pools for automatic sanitization. The Model 320 feeder is designed for permanent installation in the return line of new or existing systems and dispenses sanitizer directly into your pool or spa, downstream of all equipment. Completely enclosed systems—no escaping fumes.





MODEL 300/320 AUTOMATIC CHLORINE/BROMINE FEEDERS

Save time, reduce manual handling of chemicals

Whether you choose the freestanding Model 300 feeder or the in-line Model 320 feeder, Pentair feeders will take the work and worry out of keeping your pool sparkling clean and ready to use.

KEY FEATURES

Completely enclosed systems

Top loading

No escaping fumes.

Makes it easy to add chemicals.

MODEL 300 FEEDER

Chamber Capacity	Quantity	Weight	
1" Tablet 3" Tablet			
Maximum Erosion in 24 Hours			
Treats Pool/Spa Size in Gallons per 24 Hours*			
@ 10 ppm @ 5 ppm @ 2½ ppm			
Dimensions		21"H x 7"W x 12"D	
Service Clearance for L	id Removal	221/4"	

^{*}Using 1" trichlor tabs.




Illustration of Model 300 Feeder

CALCIUM HYPOCHLORITE IS NOT TO BE USED IN ANY FORM. Use of chemicals other than those recommended by manufacturer may be hazardous.

Simple, trouble-free designs

No special venting required.

MODEL 320 FEEDER

Chamber Capacity—1" Tablet	Bottom Feed	Top Feed	
Quantity Weight			
Chamber Capacity-3" Tablet			
Quantity Weight			
Maximum Erosion in 24 Hours	s 0.67 lbs	1.75 lbs.	
Treats Pool/Spa Size in Gallons per 24 Hours*			
@ 10 ppm @ 5 ppm @ 2½ ppm	13,400	35,000	
Dimensions			
Service Clearance for Lid Removal19"19"			

^{*}Using 1" trichlor tabs.




Illustration of Model 320 Feeder



W W W . I N G E B O M B A . C L

AV. GRECIA № 816 - LOCAL 1 - ÑUÑOA - SANTIAGO FONOS 2-22378933 2-22399559 MAIL: PROYECTOS@INGEBOMBA.CL

1620 Hawkins Ave | Sanford, NC 27330 | United States | 800.831.7133 | pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.